

# Cryptography

## Lecture 27

# Announcements

- Scholarly Paper EC due today
- “Optional” HW10 due on Wednesday, 5/15
- Final Exam Info:
  - Monday, 5/20 from 1:30-3:30pm in CSI 3117 (our regular classroom)
  - Final review sheet on course webpage, solutions are on Canvas
  - Cheat sheet posted on Canvas
  - TA OH on 5/15 TBA
  - Instructor OH 5/17 TBA

# Agenda

- This time:
  - Current Events Presentations
  - Wrapping Up
  - Final Review

# Certificates and Public-Key Infrastructure

# A single certificate authority

- $pk_{CA}$  must be distributed over an authenticated channel
  - Need only be carried out once
- Usually,  $pk_{CA}$  included in browser, browser programmed to automatically verify certificates as they arrive.
- To obtain certificate, must prove that url is legitimate.
- All parties must completely trust CA.

# Multiple certificate authorities

- Parties can choose which CA to use to obtain a certificate.
- Parties can choose which CA's certificates to trust.
- Problem: some CA may become compromised.
- Each user must manually decide which CA to trust.

# Delegation and certificate chains

- Example of certificate chain:

$$pk_A, cert_{B \rightarrow A}, pk_B, cert_{C \rightarrow B}$$

Need only trust Charlie in the above example.

- Certificate asserts that legitimate party holds public key and *that the party is trusted to issue other certificates.*
  - Delegation of CA's ability to issue certificates

# The “web of trust” model

- Model is used by PGP (“pretty good privacy”) email encryption software for distribution of public keys.
- Anyone can issue certificates to anyone else
- Each user must decide who to trust
- Example:
  - Alice holds  $pk_1, pk_2, pk_3$  for users  $C_1, C_2, C_3$
  - Bob has certificates  $cert_{C_1 \rightarrow B}, cert_{C_3 \rightarrow B}, cert_{C_4 \rightarrow B}$
- Public keys and certificates can be stored in a central database.



# Invalidating Certificates

- Expiration: Include expiration date as part of the certificate.
  - Very coarse grained method. E.g. employee leaves company but certificate does not expire for a year.
- Revocation
  - CA includes a serial number in every certificate it issues.
  - At the end of each day, the CA will generate a certificate revocation list (CRL) with the serial numbers of all revoked certificates.
  - CA will sign the CRL and the current date.
  - Signed CRL is then widely distributed.

# Putting it all together: SSL/TLS

- TLS: Transport Layer Security Protocol
  - Protocol used by browser when connecting via https
- Standardized protocol based on a precursor called SSL (Secure Socket Layer).
  - Latest SSL version: SSL 3.0
  - TLS version 1.0 released in 1999
  - TLS version 1.1 in 2006
  - TLS version 1.2 (current) in 2008
  - 50% of browsers still use TLS 1.0
- Allows a client (web browser) and a server (website) to agree on a set of shared keys and then use those keys to encrypt and authenticate their subsequent communication.
- Two parts:
  - Handshake protocol performs authenticated key exchange to establish the shared keys
  - Record-layer protocol uses shared keys to encrypt/authenticate the communication.
- Typically used for authentication of servers to clients (usually only servers—websites—have certificates).